

Centro-E-APB



Short description

Electrically operated surface-mounted exhaust air element with metal fire protection shut-off shutter for Centro-ER system for centralised ventilation

Application examples

Bathroom, Kitchen, Multiple family unit, Day room, Dining room

Article number 0084.0185

Technical data

Model	electrical
Air flow volume	20 m ³ /h / 60 m ³ /h
Minimum air flow volume	30 m ³ /h
Air direction	Air extraction
Type of voltage	Alternating current
Rated voltage	230 V
Frequency	50 Hz/60 Hz
Power consumption	3 W
I _{max}	0,9 A
Degree of protection	IP X5
Mains cable	3 x 1,5 mm ²
Installation site	Wall / Ceiling
Type of installation	Surface-mounted
System type	Centralised
Material	Synthetic material
Colour	Traffic white, similar to RAL 9016
Weight	1,45 kg
Weight including packaging	2,01 kg
Filter class	ISO Coarse 30 % (G2)
Width	236 mm
Height	236 mm
Depth	217,5 mm
Width with packaging	255 mm
Height with packaging	335 mm
Depth with packaging	255 mm
Airstream temperature at I _{Max}	40 °C
Sound pressure level	26 dB(A) / 33 dB(A) (Specifications in accordance with DIN 18017-3 at an equivalent absorption area A _L = 10 m. ²)
Packing unit	1 piece

Centro-E-APB

Range	B
GTIN (EAN)	4012799841852

Dimensioned drawing [mm]

