

# Centro-H-APB



## Short description

Electrically operated, humidity-controlled, surface-mounted exhaust air element, metal fire protection shut-off shutter for Centro-ER system for centralised ventilation.

## Application examples

Bathroom, Kitchen, Multiple family unit, Day room, Dining room

Article number 0084.0188

## Technical data

Model	electrical
Air flow volume	20 m <sup>3</sup> /h / 60 m <sup>3</sup> /h
Minimum air flow volume	30 m <sup>3</sup> /h
Air direction	Air extraction
Type of voltage	Alternating current
Rated voltage	230 V
Frequency	50 Hz/60 Hz
Power consumption	3,5 W
I <sub>max</sub>	0,9 A
Degree of protection	IP X5
Mains cable	3 x 1,5 mm <sup>2</sup>
Installation site	Wall / Ceiling
Type of installation	Surface-mounted
System type	Centralised
Material	Synthetic material
Colour	Traffic white, similar to RAL 9016
Weight	1,49 kg
Weight including packaging	2,03 kg
Filter class	ISO Coarse 30 % (G2)
Width	236 mm
Height	236 mm
Depth	217,5 mm
Width with packaging	255 mm
Height with packaging	340 mm
Depth with packaging	255 mm
Airstream temperature at I <sub>Max</sub>	40 °C
Overrun time	6 min (Overrun time available when using an optional switch (e.g. light switch))

# Centro-H-APB

Sound pressure level	26 dB(A) / 33 dB(A) (Specifications in accordance with DIN 18017-3 at an equivalent absorption area $A_L = 10 \text{ m.}^2$ )
Packing unit	1 piece
Range	B
GTIN (EAN)	4012799841883

## Dimensioned drawing [mm]

