DAR 71/6 0,75





Short description

Axial duct fan, DN 710, three-phase AC, nominal power 0.75 $\rm kW$

Application examples

Production facility, Workplace, Commercial premises, Industrial building

Article number

0073.0134

Technical data

Air flow volume	16.995 m³/h				
Rotating speed	960 1/min				
Impeller type	axial				
Speed controllable	1				
Reversing capacity	-				
Type of voltage	Three-phase AC				
Rated voltage	400 V				
Frequency	50 Hz				
Nominal output	750 W				
I _{nom}	2,01 A				
Degree of protection	IP 55				
Insulation class	F				
Pole-changeable	- Duct				
Installation site					
Installation position	Horizontal / Vertical				
Housing material	Sheet steel with epoxy coating				
Impeller material	Polyamide				
Colour	grey				
Weight	45 kg				
Weight including packaging	50 kg				
Nominal size	710 mm				
Width	810 mm				
Height	520 mm				
Depth	810 mm				
Width with packaging	830 mm				
Height with packaging	600 mm				
Depth with packaging	830 mm				
Airstream temperature at I _{Max}	-10 °C up to 50 °C				
PTC DIN 44082	M 100				

DAR 71/6 0,75



Packing unit	1 piece
Range	С
GTIN (EAN)	4012799731344

Technical data according to ErP in Best Efficiency Point (BEP)


Total efficiency η	33,4 %				
Measurement category	С				
Efficiency category	static				
Efficiency level N	40,2				
VSD necessary	No				
Year of manufacture	see rating plate				
Manufacturer's name / official registration number / manufacturer's	Maico Elektroapparate-Fabrik GmbH / Freiburg registration				
place of establishment	court, HRB 601233 / Villingen-Schwenningen				
Art. No.	0073.0134				
P _{BEP} / Air volume _{BEP} / P _{fs, BEP}	0,833 kW / 10.000 m³/h / 100 Pa				
n _{BEP}	955 1/min				
Specific ratio	≈ 1				
Information about dismantling and disposal	see mounting instructions				
Information about installation, operation and repairs	see mounting instructions				
I _{BEP}	2,01 A				
Sound power levelL _{WA7}	79 dB(A)				


Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L _{WA5} , S5	56	63	68	71	73	72	72	66	79
(dB(A))									

 L_{WA5} = free inlet sound power level in dB.

Characteristic curve





Dimensioned drawing [mm]



