

DRD H 63/6



Short description

Centrifugal roof fan, horizontal air outlet, nominal power 1.1 kW, three-phase AC

Application examples

Production facility, Workplace, Commercial premises

Article number 0073.0058

Technical data

Air flow volume	13.676 m ³ /h
Rotating speed	970 1/min
Impeller type	radial
Speed controllable	✓
Reversing capacity	–
Type of voltage	Three-phase AC
Rated voltage	400 V
Frequency	50 Hz
Nominal output	1.100 W
I _{nom}	2,9 A
Degree of protection	IP 55
Insulation class	F
Pole-changeable	–
Installation site	Roof
Installation position	vertical
Housing material	Sheet steel, galvanised
Impeller material	Sheet steel, galvanised
Colour	grey
Weight	120 kg
Weight including packaging	128 kg
Nominal size	630 mm
Width	930 mm
Height	930 mm
Depth	930 mm
Width with packaging	1.040 mm
Height with packaging	1.040 mm
Depth with packaging	1.160 mm
Airstream temperature at I _{Max}	-20 °C up to 80 °C
PTC DIN 44082	M 100

DRD H 63/6


Packing unit	1 piece
Range	C
GTIN (EAN)	4012799730583

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L_{WA5, S5} (dB(A))	57	78	80	83	80	81	78	66	88

L_{WA5}= free inlet sound power level in dB.

Characteristic curve



DRD H 63/6

Dimensioned drawing [mm]

