

DZF 35/64 BH



Short description

Airotherm three-phase AC, pole-changeable modular system for air heating

Application examples

Office, Restaurant, Fitness room, Workplace, Showroom

Article number 0085.0033

Technical data

Air flow volume	700 m ³ /h / 1.100 m ³ /h
Rotating speed	900 1/min / 1.400 1/min
Rated voltage	400 V
Frequency	50 Hz
Power consumption	125 W / 170 W
I _{nom}	0,4 A / 0,5 A
I _{max}	0,4 A / 0,5 A
Degree of protection	IP 55
Pole-changeable	✓
Mains cable	5 x 1,5 mm ²
Installation site	Wall
Type of installation	Recessed-mounted
Installation position	horizontal
Housing material	Sheet steel, galvanised
Weight	10 kg
Weight including packaging	11,39 kg
Nominal size	350 mm
Width with packaging	445 mm
Height with packaging	335 mm
Depth with packaging	445 mm
Packing unit	1 piece
Range	C
GTIN (EAN)	4012799850335

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L _{WA8, high} (dB(A))	-	-	-	-	-	-	-	-	70

DZF 35/64 BH

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
$L_{WA8, low}$ (dB(A))	-	-	-	-	-	-	-	-	60

L_{WA8} = housing and free outlet sound power level in dB.

Dimensioned drawing [mm]

