

DZQ 45/4 B Ex t



Short description

Axial wall-mounted fan with square wall plate, DN450, three-phase AC, explosion-proof, medium: dust

Article number 0083.0213

Technical data

Model	Square wall plate
Air flow volume	6.400 m ³ /h
Rotating speed	1.425 1/min
Speed controllable	✓
Reversing capacity	✓
Type of voltage	Three-phase AC
Rated voltage	400 V
Frequency	50 Hz
Nominal output	330 W
cosφ	0,67
I _{nom}	0,7 A
I _{max} at U _{Nominal}	1,1 A
Degree of protection	IP 64
Insulation class	F
Type of installation	Surface-mounted
Material	Sheet steel, galvanised
Colour	galvanised
Weight	16,5 kg
Weight including packaging	19,7 kg
Nominal size	450 mm
Width	630 mm
Height	630 mm
Depth	269 mm
Width with packaging	655 mm
Height with packaging	655 mm
Depth with packaging	320 mm
EX designation in accordance with the ATEX Directive	Ex II 2 D
EX designation in accordance with standard	Ex tb IIIB T135°C Db IP64 X / Ex h IIIB T135°C Db X
Ta ambient temperature	-20 °C ≤ Ta ≤ +40 °C

DZQ 45/4 B Ex t


I _A /I _N	4,5
Time t _A	110 sek
Operating mode	S1
PTC DIN 44082	M 100
EC type examination certificate	TÜV-A 19 ATEX0102 X, IECEx EPS 19.0018X
Temperature class	T135°C
Temperature class of insulating materials Th. Cl.	155 (F)
Packing unit	1 piece
Range	C
GTIN (EAN)	4012799832133

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L _{WA7, high} (dB(A))	-	-	-	-	-	-	-	-	82

L_{WA7}= housing and free inlet sound power level in dB.

Characteristic curve



DZQ 45/4 B Ex t

Dimensioned drawing [mm]

