

ER-APB 100 F



Short description

Surface-mounted fan with metal fire protection shut-off device for air extraction, air volume 100 m³/h, with light control

Application examples

Bathroom, Kitchen, Multiple family unit, Day room, Dining room

Article number 0084.0178

Technical data

Model	Light control
Air flow volume	100 m ³ /h
Rotating speed	1.850 1/min
Air direction	Air extraction
Speed controllable	–
SEC average	-21,24 kWh/(m ² *a)
Rated voltage	230 V
Frequency	50 Hz
Power consumption	29 W
I _{max}	0,15 A
Degree of protection	IP X5
Mains cable	3 x 1,5 mm ²
Installation site	Wall / Ceiling
Type of installation	Surface-mounted
System type	Decentralised
Material	Synthetic material
Colour	Traffic white, similar to RAL 9016
Weight	2,1 kg
Weight including packaging	2,66 kg
Filter class	ISO Coarse 30 % (G2)
Fire protection	yes
Shut-off device	Integrated metal shut-off device with release mechanism
Connection diameter	75 mm / 80 mm
Width	236 mm
Height	236 mm
Depth	217,5 mm
Width with packaging	255 mm
Height with packaging	335 mm
Depth with packaging	255 mm

ER-APB 100 F

Airstream temperature at I_{Max}	40 °C
Overrun time	6 min
Start delay	50 s
Sound pressure level	49 dB(A) (Specifications in accordance with DIN 18017-3 at an equivalent absorption area $A_L = 10 \text{ m}^2$)
Approval number	Z-51.1-45
Packing unit	1 piece
Range	B
GTIN (EAN)	4012799841784

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
$L_{WA7, \text{high}}$ (dB(A))	-	-	-	-	-	-	-	-	53

L_{WA7} = housing and free inlet sound power level in dB.

Characteristic curve



ER-APB 100 F

Dimensioned drawing [mm]

