

ESR 20 S



Short description

Sound-insulated ventilation box with swivelling fan, DN 200, single-phase AC

Article number 0080.0229

Technical data

Air flow volume	890 m ³ /h
Rotating speed	2.490 1/min
Speed controllable	–
Type of voltage	Alternating current
Rated voltage	230 V
Nominal output	190 W
I _{nom}	0,84 A
I _{max}	0,9 A
Weight	20
Swivelling fan	–
Nominal size	200 mm
Airstream temperature at nominal current	55 °C
Ambient temperature	55 °C
Packing unit	1 piece
Range	C
GTIN (EAN)	4012799802297

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L_{WA5}, S5 (dB(A))	–	46	56	55	48	47	46	38	60
L_{WA6}, S5 (dB(A))	–	54	63	72	69	68	62	55	75
L_{WA2}, S5 (dB(A))	–	46	48	54	37	31	29	23	56


L_{WA2}= housing sound power level in dB.

L_{WA5}= free inlet sound power level in dB.

L_{WA6}= free outlet sound power level in dB.

ESR 20 S

Characteristic curve



Dimensioned drawing [mm]

