RSR 8/50





Short description

Tubular sound absorber with 50 mm sound absorbing cover, length: 1,000 mm, DN 80

Application examples

Showroom, Restaurant, Theatre, Production site, Industrial building

Article number 0092.0320


Technical data

Model	50 mm cound absorbing cover	
Material	50 mm sound absorbing cover Aluminium	
Weight	1,5 kg	
Weight including packaging	2 kg	
Nominal size	80 mm	
Width	189,5 mm	
Height	189,5 mm	
Depth	1.120 mm	
Width with packaging	220 mm	
Height with packaging	220 mm	
Depth with packaging	1.195 mm	
Insertion loss at 63 Hz	3 dB	
Insertion loss at 125 Hz	13 dB	
Insertion loss at 250 Hz	19 dB	
Insertion loss at 500 Hz	30 dB	
Insertion loss at 1 kHz	47 dB	
Insertion loss at 2 kHz	58 dB	
Insertion loss at 4 kHz	33 dB	
Insertion loss at 8 kHz	28 dB	
Total insertion loss		
Insertion loss note		
Sound insulation	yes	
Packing unit	1 piece	
Range	С	
GTIN (EAN)	4012799923206	

RSR 8/50




Characteristic curve Pressure losses



- ① Pressure loss in Pa/m sound absorber
- ② Duct diameter
- 3 Velocity of flow

Dimensioned drawing [mm]



RSR 8/50



Α	В	С	D	E
80	180	1.120	79,5	189,5