SDE 12





Short description

Slide-in sound absorber including all plugs, length: 50 mm, DN 125 $\,$

Application examples

Single-family house, Multiple family unit, Office, Commercial premises, Waiting room

Article number 0044.0215


Technical data

Installation site	Duct
Material	PU foam
Weight	0,07 kg
Weight including packaging	0,1 kg
Nominal size	125 mm
Suitable for nominal size	125
External diameter	127 mm
Width	120 mm
Height	120 mm
Depth	50 mm
Width with packaging	120 mm
Height with packaging	120 mm
Depth with packaging	50 mm
Insertion loss at 63 Hz	5 dB / 2 dB / 1 dB
Insertion loss at 125 Hz	6 dB / 2 dB / 1,5 dB
Insertion loss at 250 Hz	5 dB / 2,5 dB / 1,5 dB
Insertion loss at 500 Hz	5 dB / 3 dB / 2,5 dB
Insertion loss at 1 kHz	12 dB / 8,5 dB / 6 dB
Insertion loss at 2 kHz	13 dB / 8 dB / 5 dB
Insertion loss at 4 kHz	19 dB / 14 dB / 11 dB
Insertion loss at 8 kHz	21 dB / 19 dB / 18 dB
Total insertion loss	
Insertion loss note	indications for 1, 3 and 5 openings
Packing unit	1 piece
Range	С
GTIN (EAN)	4012799442158

SDE 12



Characteristic curve



① Number of openings