


WS 120 Trio LL



Short description

Compact and quiet centralised ventilation unit with longitudinal flow, exhaust air to the left, with effective heat and humidity recovery, EC fans with constant volumetric flow regulation, connection of a channel system, 40-120 m³/h

Application examples

Apartments, Terraced houses, Doctor's practice, Hotels, Retirement home

Article number 0095.0655

Technical data

Model	Longitudinal flow, exhaust air to the left
Air flow volume	40 m ³ /h - 120 m ³ /h
Rotating speed	2.200 1/min
SEC average	-36,82 kWh/(m ² *a)
Energy efficiency class	A
Type of voltage	Alternating current
Rated voltage	230 V
Frequency	50 Hz/60 Hz
SPI value in accordance with DIN EN 13141-7 (A7)	0,29 Wh/m ³
Power consumption in accordance with DIN EN 13141-7 (A7)	20 W
Stand-by power consumption	< 1 W
I _{max}	1 A
Degree of protection	IP 00
DIBT approval	Applied for
Installation site	Wall / ceiling
System type	Centralised
Material	EPP plastic / galvanised sheet steel
Housing material	Plastic EPP
Heat exchanger material	Synthetic material
Colour	black / traffic white (RAL 9016)
Weight	25 kg
Weight including packaging	28 kg
Filter class	ISO ePM10 ≥ 50 % (M5) / ISO ePM1 ≥ 60 % (F7)
Width	600 mm
Height	210 mm
Depth	1.000 mm
Width with packaging	720 mm
Height with packaging	300 mm
Depth with packaging	1.120 mm

WS 120 Trio LL

Airstream temperature at I _{Max}	-20 °C up to 50 °C
Max. degree of heat provision in accordance with DIN EN 13141-7 (A7)	81 %
Heat exchanger construction type	Enthalpy cross-counterflow
Humidity recovery with enthalpy heat exchanger in accordance with DIN EN 13141-7 (A2)	69 %
Position – exhaust air	left
Bypass	No
Frost protection	No
Enthalpy heat exchanger	yes
Antifreeze circuit	yes
Summer circuit	ECO exhaust air / ECO supply air
Filter monitoring	with time control
Humidity control	integrated
CO ₂ regulation	Trio CO2 E, Trio CO2 I
Air quality control (optional)	Trio VOC E, Trio VOC I
KNX connection (optional)	K-SM
MODBUS interface	integrated
Control unit included in scope of delivery.	RLS 1 WR, App
Control unit (optional)	RLS T2 WS, RLS G1 WS
EnOcean wireless integration (optional)	E-SM
Mobile control	yes
Housing emission sound pressure level	32 dB (Spacing 1m, sound absorption 10 m ²)
Packing unit	1 piece
Range	K
GTIN (EAN)	4012799956556

Sound power level in octave range

	63 Hz	125 Hz	250 Hz	500 Hz	1 kHz	2 kHz	4 kHz	8 kHz	Total
L_{WA2} (dB(A))	16	22	23	28	33	28	17	11	40
L_{WA5} (dB(A))	11	25	29	21	23	20	10	9	37
L_{WA6} (dB(A))	10	24	30	20	30	24	11	9	38

L_{WA2}= housing sound power level in dB.

L_{WA5}= free inlet sound power level in dB.

L_{WA6}= free outlet sound power level in dB.

Operating point: Air volume 84 m³/h and external pressure 50 Pa

WS 120 Trio LL

- ⑥ View from below
- ⑦ Filter covers
- ⑧ Mains connection
- ⑨ Connection cable for control panel
- ⑩ USB
- ⑪ Ceiling / wall