

Duo A-SE

Features

- Continuous air exchange thanks to integrated cross-counterflow heat exchanger.
- If necessary, pure supply air or exhaust air operation can also be set. With 2 integrated G3 filters, M6 filter optional.
- Visually appealing design.
- Housing and wall sleeves made 100% from sound-absorbing EPP
- Optional accessories suited to various wall thicknesses.

The components of the Duo single room ventilation unit with heat recovery:

Needed:

- Duo A-SE or AO-SE installation kit (for surface mounting) or Duo Z-SE or ZO-SE installation kit (for recess mounting) comprising:
 - Fans
 - Heat exchanger
 - Controller
 - Regulation technology
- Duo A-SR shell installation kit for Duo Z-SR shell installation kit comprising:
 - Two wall sleeves (outer Ø 125 mm, inner Ø 90 mm, length 500 mm) made from EPP, each with two plaster protective covers
 - Duo A-SR: Drilling template with centring
 - Duo Z-SR: Installation box (width x height x depth: 830 x 417 x 93 mm) with integrated drilling template, connection for flexible ducts
- Duo KWS E combination wall socket (stainless steel, brushed) or Duo KWS W combination wall socket (white stainless steel, powder coated)

Optional:

- Duo G3 replacement air filter
- Duo M6 pollen replacement air filter