

<b>a) Lieferant</b> supplier's name		Maico Elektroapparate-Fabrik GmbH						
<b>b) Modellkennung (Code)</b> supplier model identifier (code)		WS 120 Trio LRV (0095.0658)						
<b>c) Spezifischer Energieverbrauch</b> specific energy consumption SEC class - climate zone „average“	<b>SEC</b>	kalt / cold	mittel / average		warm / warm		kWh / (m <sup>2</sup> ·a)	
		-78,74	-36,82		-12,81			
		A						
<b>d) Typ</b> typology	RVU		x	BVU		x		
	NRVU		-	UVU		-		
<b>e) Art des eingebauten / einzubauenden Antriebes</b> type of drive installed / intended to be installed	multi-speed		-		installed		X	
	VSD		x	intended to be instal.		-		
<b>f) Art des Wärmerückgewinnungssystems (WRG)</b> type of heat recovery system	rekuperativ / recuperative		x	regenerativ / regenerative		-		
							keines / none	
						-		
<b>g) Temperaturänderungsgrad der WRG</b> thermal efficiency of heat recovery	$\eta_t$	80,9				%		
<b>h) Höchster Luftvolumenstrom</b> maximum flow rate					120		m <sup>3</sup> /h	
<b>i) Elektrische Eingangsleistung Ventilatorantrieb</b> electric power input of the fan drive					24,5		W	
<b>j) Schalleistungspegel</b> sound power level	$L_{WA..}$					39,9		dB[A]
<b>k) Bezugs-Luftvolumenstrom</b> reference flow rate					0,02333		m <sup>3</sup> /s	
<b>l) Bezugsdruckdifferenz</b> reference pressure difference					50		Pa	
<b>m) Spezifische Eingangsleistung</b> specific power input	<b>SPI</b>					0,29		W/(m <sup>3</sup> /h)
<b>n) Steuerungsfaktor und Steuerungstypologie</b> control factor and control typology	CTRL		MISC		X-Value		-	
	0,85		1,1		2			
<b>o) Innere Höchstleckluft rate / Äußere Höchstleckluft rate</b> max. internal leakage rate / max. external leakage rate	innere / internal	1,1	äußere / external		1,7	%		
<b>p) Mischrate</b> mixing rate					-		%	
<b>q) Lage und Beschreibung optische Filterwarnanzeige</b> position and description of visual filter warning	LED - replace the filter continuously to preserve the device properties							
<b>r) Anweisungen für Anbringung regelbarer AUL- / ABL-Gitter</b> instructions to install regulated supply/exhaust grilles	-							
<b>s) Internetadresse für Anweisungen zur Zerlegung/Demontage</b> internet address for disassembly instructions	www.maico-ventilatoren.com							
<b>t) Druckschwankungsempfindlichkeit Luftstrom</b> airflow sensitivity to pressure variations at -20 Pa / +20 Pa					-		%	
<b>u) Luftdichtheit zwischen innen und außen</b> indoor / outdoor air tightness					-		m <sup>3</sup> /h	
<b>v) Jährlicher Stromverbrauch</b> annual electricity consumption	<b>AEC</b>					3,1		kWh/(m <sup>2</sup> ·a)
<b>w) Jährliche Einsparung an Heizenergie</b> annual heating saved	<b>AHS</b>	kalt/cold	mittel / average		warm / warm		kWh/(m <sup>2</sup> ·a)	
		85,7	43,8		19,8			