

a) Lieferant supplier's name		Maico Elektroapparate-Fabrik GmbH							
b) Modellkennung (Code) supplier model identifier (code)		ERR 10/2 EC (0073.0583)							
c) Spezifischer Energieverbrauch specific energy consumption SEC class - climate zone „average“	SEC	kalt / cold	mittel / average		warm / warm		kWh / (m ² ·a)		
		-53	-26		-10				
		C							
d) Typ typology		RVU	x	BVU	–				
		NRVU	–		UVU	x			
e) Art des eingebauten / einzubauenden Antriebes type of drive installed / intended to be installed		single speed	–		multi-speed	–		installed	x
		2-speed	–		VSD	x	intended to be instal.		–
f) Art des Wärmerückgewinnungssystems (WRG) type of heat recovery system		rekuperativ / recuperative	–		regenerativ / regenerative	–		keines / none	x
g) Temperaturänderungsgrad der WRG thermal efficiency of heat recovery	η_t	–						%	
h) Höchster Luftvolumenstrom maximum flow rate		340						m ³ /h	
i) Elektrische Eingangsleistung Ventilatorantrieb electric power input of the fan drive		122						W	
j) Schalleistungspegel sound power level	$L_{WA..}$	60						dB[A]	
k) Bezugs-Luftvolumenstrom reference flow rate		0,0661						m ³ /s	
l) Bezugs-Druckdifferenz reference pressure difference		50						Pa	
m) Spezifische Eingangsleistung specific power input	SPI	0,176						W/(m ³ /h)	
n) Steuerungsfaktor und Steuerungstypologie control factor and control typology		CTRL	MISC		X-Value		–		
		0,65	1,1		2				
o) Innere Höchstluftrate / Äußere Höchstluftrate max. internal leakage rate / max. external leakage rate		innere / internal	–	äußere / external	–		%		
p) Mischrate mixing rate		–						%	
q) Lage und Beschreibung optische Filterwarnanzeige position and description of visual filter warning		–							
r) Anweisungen für Anbringung regelbarer AUL- / ABL-Gitter instructions to install regulated supply/exhaust grilles		It is necessary to provide inlet openings suited to the flow needs of the ventilation unit							
s) Internetadresse für Anweisungen zur Zerlegung/Demontage internet address for disassembly instructions		www.maico-ventilatoren.com							
t) Druckschwankungsempfindlichkeit Luftstrom airflow sensitivity to pressure variations at -20 Pa / +20 Pa		–						%	
u) Luftdichtheit zwischen innen und außen indoor / outdoor air tightness		–						m ³ /h	